

AGRICULTURAL & OFF-ROAD TIRES





barkleytire.com

**DELIVERING PERFORMANCE
DRIVING GROWTH**

BARKLEY

TABLE OF
CONTENTS

ABOUT BARKLEY	4	DUMP TRUCKS	 54
TRACTORS	 6	BLB02S	54
BLA01	8	BLB03S	56
BLA02	14	BLM06S	56
BLA03	18	SAND	 58
HARVESTERS	 22	BLD08	58
BLA07	22	MOBILE CRANES	 58
BLA05	26	BLM02	58
BLA09	28	MINING	 60
SPRAYERS	 30	BLM05	60
BLA01	30	GRADERS	 60
BLA08	32	BBE02	60
FLOATERS	 34	BBE03	62
BLAF1	34		
BLF01	36		
TRAILERS	 40		
BLT03	40		
BL606	42		
INDUSTRIAL	 44		
BLA04	44		
BLA06	46		
LOADERS & DOZERS	 50		
BLB01	50		
BLB05S	50		
BLB06S+	52		
BLB07S+	52		
BBE01	54		



TRUCK & BUS

AGRICULTURE

OFF-ROAD

ABOUT BARKLEY

Count on the best price per kilometer, count on Barkley. Enjoy best value tires, expertly crafted in Europe & Asia. With fast delivery and low minimum order quantities, backed by our knowledgeable support.

In today's economic landscape, the significance of price and value resonates deeply with all of us, alongside an unwavering commitment to quality and safety.

At Barkley, we stand firm in our pledge to deliver high-quality tires at competitive prices, ensuring that every purchase represents both value and reliability.

Our customers take pride in our products, finding satisfaction in the craftsmanship and dedication that

goes into each tire we produce. Moreover, we prioritise equipping you with the professional knowledge necessary to make informed decisions about your tire needs.

We consider our customers part of the Barkley family, providing steadfast support and guidance every step of the way as you navigate through the myriad of options to find the perfect tires for your business.

DELIVERING PERFORMANCE DRIVING GROWTH



AGRICULTURAL TIRES

High load-bearing capacity, excellent quality and wide modern pattern with superb self-cleansing properties.



OFF-ROAD TIRES

Strong, flexible shock absorbing tires that improve drive comfort and provide lower fuel consumption.



CONSISTENT QUALITY

We work with carefully selected manufacturers offering consistent quality across our ranges.



LOW MINIMUM ORDERS

We offer lower minimum order quantities at very competitive prices, direct to your door.



EXPERT SUPPORT

We provide ongoing technical support and knowledgeable guidance to all of our customers.



FACTORY VISITS

Get in touch to arrange a guided tour around our factories in either Serbia, Thailand or China.

High load-bearing capacity, excellent quality and a wide modern pattern with superb self-cleansing properties!

Fertilising, sowing, harvesting, ploughing, tractor tires must meet strict requirements because they deal with all kinds of conditions.

Our tires will help you to maximise the potential of your harvest. By using top quality tires at a very competitive price! Technology never stands still. Certainly when it comes to Agriculture. Stronger, faster and heavier tractors that must travel long distances on roads at higher speeds. Naturally, your tractor tires must also deal with these new demands. We can offer you tires with the traction, life-span and soil protection you are looking for. Like the BLA07 - our large-volume tire for tractors.



AGR/
AGRICULTURAL





BLA01

R-1 / R-1W

- ✓ Deep lugs, low slip and optimized rubber compounds help reduce wear for exceptionally long tire life.
- ✓ Good self-cleaning properties help keep the tread pattern free of mud, resulting in less slip, even in difficult conditions.
- ✓ Multiple types of rubber are designed with tread compound, providing excellent wear and fatigue resistance.

AVAILABLE SIZES

280/85R24	340/85R36	420/85R30	520/85R38
320/85R24	340/85R38	420/85R34	520/85R42
320/85R28	380/85R24	420/85R38	420/80R46
320/85R32	380/85R28	460/85R30	480/80R42
320/85R36	380/85R30	460/85R34	480/80R46
340/85R24	380/85R34	460/85R38	420/90R30
340/85R28	420/85R24	460/85R42	320/90R46
340/85R32	420/85R28	460/85R46	



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
280/85R24	BLA01	115/112	A8/B	W9 W10	TL	1215	160	1086	282	39	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
320/85R24	BLA01	122/119	A8/B	W9 W10 W11	TL	1500	160	1154	319	41	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
320/85R28	BLA01	124/121	A8/B	W9 W10 W11	TL	1600	160	1255	319	41	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
320/85R32	BLA01	142/139	A8/B	W9 W10 W11	TL	2650	400	1357	319	41	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
320/85R36	BLA01	128/125	A8/B	W9 W10 W11	TL	1800	160	1458	319	41	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
340/85R24	BLA01	125/122	A8/B	W11 W12	TL	1650	160	1188	343	42	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
340/85R28	BLA01	127/124	A8/B	W11 W12	TL	1750	160	1289	343	42	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
340/85R32	BLA01	142/139	A8/B	W11 W12	TL	2650	360	1391	343	42	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
340/85R36	BLA01	132/129	A8/B	W11 W12	TL	2000	160	1492	343	42	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
340/85R38	BLA01	133/130	A8/B	W11 W12	TL	2060	160	1543	343	42	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
380/85R24	BLA01	131/128	A8/B	W11 W12 W13	TL	1950	160	1256	380	45	10km/h
											30km/h
											40km/h
											50km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
865	1005	1145	1290	1430	1575					
715	830	945	1065	1180	1300					
665	775	885	995	1105	1215					
615	715	815	915	1015	1120					
1070	1245	1420	1595	1770	1950					
880	1025	1170	1315	1460	1605					
825	960	1095	1230	1365	1500					
745	870	990	1115	1235	1360					
1140	1330	1515	1705	1890	2080					
940	1090	1245	1400	1555	1710					
880	1020	1165	1310	1455	1600					
795	925	1055	1185	1315	1450					
1205	1410	1615	1825	2030	2200	2445	2580	2820	3065	3270
990	1160	1330	1500	1670	1810	2010	2125	2320	2520	2690
925	1085	1245	1400	1560	1695	1880	1985	2170	2355	2515
850	995	1140	1285	1430	1555	1725	1820	1990	2160	2305
1285	1495	1705	1915	2125	2340					
1055	1230	1405	1575	1750	1925					
990	1150	1310	1475	1635	1800					
905	1055	1200	1350	1500	1650					
1175	1370	1565	1755	1950	2145					
970	1125	1285	1445	1605	1765					
905	1055	1200	1350	1500	1650					
825	960	1095	1230	1365	1500					
1250	1455	1660	1865	2070	2275					
1025	1195	1365	1530	1700	1870					
960	1120	1275	1435	1590	1750					
880	1020	1165	1310	1455	1600					
1270	1480	1685	1925	2135	2340	2580	2720	2995	3235	3445
1045	1215	1385	1585	1755	1925	2125	2235	2465	2660	2835
980	1135	1295	1480	1640	1800	1985	2090	2305	2490	2650
895	1040	1190	1360	1505	1650	1820	1915	2110	2280	2430
1430	1660	1895	2130	2365	2600					
1175	1365	1560	1750	1945	2140					
1100	1280	1460	1640	1820	2000					
1015	1180	1350	1515	1680	1850					
1470	1710	1950	2190	2430	2675					
1210	1405	1605	1800	2000	2200					
1130	1315	1500	1685	1870	2060					
1045	1215	1385	1555	1725	1900					
1390	1620	1850	2075	2305	2535					
1145	1330	1520	1705	1895	2085					
1070	1245	1420	1595	1770	1950					
990	1150	1310	1475	1635	1800					

Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
380/85R28	BLA01	133/130	A8/B	W11 W12 W13	TL	2060	160	1357	380	45	10km/h
											30km/h
											40km/h
											50km/h
380/85R30	BLA01	135/132	A8/B	W11 W12 W13	TL	2180	160	1408	380	45	10km/h
											30km/h
											40km/h
											50km/h
380/85R34	BLA01	147/147	A8/B	W11 W12 W13	TL	3075	300	1510	380	45	10km/h
											30km/h
											40km/h
											50km/h
420/85R24	BLA01	137/134	A8/B	W13 W14L W15L	TL	2300	160	1324	418	48	10km/h
											30km/h
											40km/h
											50km/h
420/85R28	BLA01	139/136	A8/B	W13 W14L W15L	TL	2430	160	1425	418	48	10km/h
											30km/h
											40km/h
											50km/h
420/85R30	BLA01	140/137	A8/B	W13 W14L W15L	TL	2500	160	1476	418	48	10km/h
											30km/h
											40km/h
											50km/h
420/85R34	BLA01	142/139	A8/B	W13 W14L W15L	TL	2650	160	1578	418	48	10km/h
											30km/h
											40km/h
											50km/h
420/85R38	BLA01	144/141	A8/B	W13 W14L W15L	TL	2800	160	1679	418	48	10km/h
											30km/h
											40km/h
											50km/h
460/85R30	BLA01	145/142	A8/B	W14L W15L W16L	TL	2900	160	1544	455	51	10km/h
											30km/h
											40km/h
											50km/h
460/85R34	BLA01	147/144	A8/B	W14L W15L W16L	TL	3075	160	1646	455	51	10km/h
											30km/h
											40km/h
											50km/h
460/85R38	BLA01	149/146	A8/B	W14L W15L W16L	TL	3250	160	1747	455	51	10km/h
											30km/h
											40km/h
											50km/h
460/85R42	BLA01	150/147	A8/B	W14L W15L W16L	TL	3350	160	1849	455	51	10km/h
											30km/h
											40km/h
											50km/h
460/85R46	BLA01	152/149	A8/B	W14L	TL	3550	160	1943	464	51	10km/h
											30km/h
											40km/h
											50km/h
460/85R46	BLA01	158/155	A8/B	W14L	TL	4250	240	1943	464	51	10km/h
											30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
1470	1710	1950	2190	2430	2675					
1210	1405	1605	1800	2000	2200					
1130	1315	1500	1685	1870	2060					
1045	1215	1385	1555	1725	1900					
1555	1810	2065	2320	2575	2830					
1280	1490	1700	1910	2120	2330					
1195	1395	1590	1785	1980	2180					
1100	1280	1460	1640	1820	2000					
1610	1900	2190	2435	2725	2975	3265	3510	3845		
1325	1565	1800	2005	2245	2450	2685	2890	3165		
1240	1465	1685	1875	2100	2290	2515	2705	2960		
1240	1465	1685	1875	2100	2290	2515	2705	2960		
1640	1910	2180	2450	2720	2990					
1350	1570	1795	2015	2235	2460					
1265	1470	1675	1885	2090	2300					
1165	1355	1545	1735	1925	2120					
1735	2015	2300	2585	2870	3155					
1430	1660	1895	2130	2365	2600					
1335	1555	1770	1990	2210	2430					
1230	1430	1635	1835	2035	2240					
1705	1960	2255	2545	2830	3125	3415	3640			
1405	1615	1855	2095	2330	2570	2810	2995			
1315	1510	1735	1960	2180	2405	2630	2800			
1315	1510	1735	1960	2180	2405	2630	2800			
1785	2080	2370	2665	2955	3250					
1470	1710	1950	2190	2430	2675					
1375	1600	1825	2050	2275	2500					
1265	1470	1675	1885	2090	2300					
1765	2030	2330	2635	2935	3235	3540	3770			
1455	1670	1920	2170	2415	2660	2915	3100			
1360	1565	1795	2030	2260	2490	2725	2900			
1360	1565	1795	2030	2260	2490	2725	2900			
1890	2200	2510	2820	3130	3445					
1555	1810	2065	2320	2575	2835					
1455	1695	1930	2170	2410	2650					
1335	1555	1770	1990	2210	2430					
2000	2325	2655	2980	3310	3640					
1645	1915	2185	2455	2725	2995					
1540	1790	2040	2295	2545	2800					
1415	1645	1875	2110	2340	2575					
2070	2410	2750	3090	3430	3770					
1705	1980	2260	2540	2820	3100					
1595	1855	2115	2375	2635	2900					
1455	1695	1930	2170	2410	2650					
2195	2555	2915	3275	3635	3995					
1805	2105	2400	2695	2990	3290					
1690	1965	2240	2520	2795	3075					
1540	1790	2040	2295	2545	2800					
2320	2700	3080	3460	3840	4225					
1910	2220	2535	2845	3160	3475					
1785	2080	2370	2665	2955	3250					
1650	1920	2190	2460	2730	3000					
2395	2785	3175	3570	3960	4355					
1965	2290	2610	2935	3255	3580					
1840	2140	2445	2745	3045	3350					
1690	1965	2240	2520	2795	3075					
2535	2950	3365	3780	4195	4615					
2085	2425	2770	3110	3450	3795					
1950	2270	2590	2910	3230	3550					
1785	2080	2370	2665	2955	3250					
2595	2980	3425	3865	4305	4750	5190	5525			
2135	2450	2815	3180	3545	3905	4270	4545			
1995	2295	2635	2975	3315	3655	3995	4250			
1820	2090	2400	2710	3020	3330	3640	3875			

Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
520/85R38	BLA01	155/152	A8/B	DW16L DW18L	TL	3875	160	1849	516	54	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
520/85R42	BLA01	160/160	A8/B	DW16L DW18L	TL	4500	240	1849	516	54	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
520/85R42	BLA01	157/154	A8/B	DW16L DW18L	TL	4125	160	1951	516	54	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
420/80R46	BLA01	151/148	A8/B	W12 W13	TL	3450	240	1840	418	47	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
480/80R42	BLA01	151/151	A8/B	DD16L DW16L W16L DW16A' W16A'	TL	3450	160	1835	479	49	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
480/80R42	BLA01	156/156	A8/B	DD16L DW16L W16L DW16A' W16A'	TL	4000	240	1835	479	49	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
480/80R46	BLA01	158/158	A8/B	DD16L DW16L W16L DW16A' W16A'	TL	4250	240	1936	479	49	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
420/90R30	BLA01	142/139	A8/B	DW13 W14L	TL	2650	160	1518	418	48	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
420/90R30	BLA01	147/144	A8/B	DW13 W14L	TL	3075	240	1518	418	48	10km/h
											30km/h
											40km/h
											50km/h
											50km/h
320/90R46	BLA01	146/143	A8/B	W9 W10 W11	TL	3000	320	1744	319	37	10km/h
											30km/h
											40km/h
											50km/h
											50km/h

Pressure(kPa)-Load per tyre in kg											
60	80	100	120	140	160	200	240	280	320	360	
2765	3220	3675	4125	4580	5035						
2275	2650	3025	3395	3770	4145						
2130	2480	2825	3175	3525	3875						
1950	2270	2590	2910	3230	3550						
2745	3155	3625	4095	4560	5030	5495	5850				
2260	2600	2985	3370	3755	4140	4525	4815				
2115	2430	2790	3150	3510	3870	4230	4500				
2115	2430	2790	3150	3510	3870	4230	4500				
2945	3430	3910	4395	4875	5360						
2425	2820	3215	3615	4010	4410						
2265	2640	3010	3380	3750	4125						
2060	2400	2735	3075	3410	3750						
2760	3255	3755	4180	4675	5100	5595	6020	6585	7085		
2270	2680	3085	3435	3845	4195	4605	4955	5420	5830		
2125	2505	2885	3215	3595	3920	4305	4630	5065	5450		
1950	2300	2650	2950	3300	3600	3950	4250	4650	5000		
2105	2420	2780	3135	3495	3855	4215	4485				
1730	1990	2285	2580	2875	3170	3465	3690				
1620	1860	2135	2415	2690	2965	3240	3450				
1480	1700	1950	2205	2455	2705	2960	3150				
2465	2870	3270	3675	4080	4485						
2025	2360	2690	3025	3355	3690						
1895	2205	2515	2825	3135	3450						
1895	2205	2515	2825	3135	3450						
2440	2805	3220	3640	4055	4470	4885	5200				
2010	2310	2650	2995	3335	3680	4020	4280				
1880	2160	2480	2800	3120	3440	3760	4000				
1880	2160	2480	2800	3120	3440	3760	4000				
2595	2980	3425	3865	4305	4750	5190	5525				
2135	2450	2815	3180	3545	3905	4270	4545				
1995	2295	2635	2975	3315	3655	3995	4250				
1995	2295	2635	2975	3315	3655	3995	4250				
1890	2200	2510	2820	3130	3445						
1555	1810	2065	2320	2575	2835						
1455	1695	1930	2170	2410	2650						
1335	1555	1770	1990	2210	2430						
1875	2155	2475	2795	3115	3435	3755	3995				
1545	1775	2035	2300	2565	2825	3090	3290				
1445	1660	1905	2150	2395	2640	2890	3075				
1315	1510	1735	1960	2180	2405	2630	2800				
1520	1790	2065	2300	2570	2805	3080	3315	3625	3900		
1250	1475	1700	1890	2115	2310	2535	2725	2985	3210		
1170	1380	1590	1770	1980	2160	2370	2550	2790	3000		
1060	1250	1440	1605	1795	1960	2150	2315	2530	2725		



BLA02

R-1W

- ✓ Outstanding long tire life thanks to the use of a wear-resistant tread compound.
- ✓ Super flat tread and large footprint help reduce soil compaction.

AVAILABLE SIZES

240/70R16	320/70R20	420/70R24	480/70R34
260/70R16	320/70R24	420/70R28	480/70R38
280/70R16	360/70R24	480/70R24	520/70R38
280/70R20	380/70R24	480/70R28	580/70R38



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
240/70R16	BLA02	104/104	A8/B	W8 W8L W9	TL	900	240	742	244	27	10km/h
											30km/h
											40km/h
											50km/h
260/70R16	BLA02	109/109	A8/B	W8 W8L W9	TL	1030	240	770	258	29	10km/h
											30km/h
											40km/h
											50km/h
280/70R16	BLA02	112/112	A8/B	W8 W8L W9 W10	TL	1120	240	798	282	30	10km/h
											30km/h
											40km/h
											50km/h
280/70R20	BLA02	116/113	A8/B	W9 W10	TL	1250	240	900	282	35.5	10km/h
											30km/h
											40km/h
											50km/h
320/70R20	BLA02	113/113	A8/B	W9 W10 W11	TL	1150	160	982	319	36	10km/h
											30km/h
											40km/h
											50km/h
320/70R24	BLA02	116/116	A8/B	W9 W10 W11	TL	1250	160	1094	319	38	10km/h
											30km/h
											40km/h
											50km/h
	BLA02	122/119	A8/B	W10 W11 W12	TL	1500	160	1152	357	42	10km/h
											30km/h
											40km/h
											50km/h
360/70R24	BLA02	127/124	A8/B	W10 W11 W12	TL	1750	240	1152	357	42	10km/h
											30km/h
											40km/h
											50km/h
380/70R24	BLA02	125/125	A8/B	W11 W12 W13	TL	1650	160	1190	380	43	10km/h
											30km/h
											40km/h
											50km/h
420/70R24	BLA02	130/127	A8/B	W12 W13 W14L	TL	1900	160	1248	418	44	10km/h
											30km/h
											40km/h
											50km/h
	BLA02	136/133	A8/B	W12 W13 W14L	TL	2240	240	1248	418	44	10km/h
											30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg											
60	80	100	120	140	160	200	240	280	320	360	
475	560	640	725	805	875	1040	1170				
390	460	525	595	660	720	850	960				
365	430	495	555	620	675	800	900				
365	430	495	555	620	675	800	900				
545	640	730	825	920	1000	1185	1335				
450	525	605	680	755	825	975	1100				
420	490	565	635	710	770	915	1030				
420	490	565	635	710	770	915	1030				
595	695	800	900	1000	1090	1290	1455				
485	570	655	740	820	895	1060	1195				
455	535	615	690	770	840	995	1120				
455	535	615	690	770	840	995	1120				
665	780	890	1005	1120	1215	1445	1625				
545	640	730	825	920	1000	1185	1335				
510	600	685	775	860	935	1110	1250				
470	550	630	710	790	860	1020	1150				
820	955	1090	1225	1360	1495						
675	785	895	1005	1115	1230						
630	735	835	940	1045	1150						
630	735	835	940	1045	1150						
890	1040	1185	1330	1475	1625						
730	850	970	1090	1210	1335						
685	800	910	1025	1135	1250						
685	800	910	1025	1135	1250						
1070	1245	1420	1595	1770	1950						
880	1025	1170	1315	1460	1605						
825	960	1095	1230	1365	1500						
745	870	990	1115	1235	1360						
1065	1225	1410	1590	1770	1955	2135	2275				
875	1005	1155	1305	1455	1605	1755	1870				
820	945	1085	1225	1365	1505	1645	1750				
750	860	990	1120	1245	1375	1500	1600				
1175	1370	1565	1755	1950	2145						
970	1125	1285	1445	1605	1765						
905	1055	1200	1350	1500	1650						
905	1055	1200	1350	1500	1650						
1355	1580	1800	2025	2245	2470						
1115	1295	1480	1660	1845	2030						
1045	1215	1385	1555	1725	1900						
960	1120	1275	1435	1590	1750						
1365	1570	1800	2035	2265	2500	2735	2910				
1125	1290	1480	1675	1865	2055	2250	2395				
1050	1205	1385	1565	1745	1925	2105	2240				
965	1110	1275	1440	1605	1770	1935	2060				

Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
420/70R28	BLA02	133/130	A8/B	W12 W13 W14L	TL	2060	160	1349	418	44	10km/h
											30km/h
											40km/h
											50km/h
											10km/h
480/70R24	BLA02	138/135	A8/B	W14L W15L W16L	TL	2360	160	1316	479	47	30km/h
											40km/h
											50km/h
											10km/h
											30km/h
480/70R28	BLA02	140/137	A8/B	W14L W15L W16L	TL	2500	160	1421	479	47	30km/h
											40km/h
											50km/h
											10km/h
											30km/h
	BLA02	145/142	A8/B	W14L W15L W16L	TL	2900	240	1421	479	47	40km/h
											50km/h
											10km/h
											30km/h
											50km/h
BLA02	151/148	A8/B	W14L W15L W16L	TL	3450	320	1421	479	47	10km/h	
										30km/h	
										40km/h	
										50km/h	
										10km/h	
480/70R34	BLA02	143/143	A8/B	W14L W15L W16L	TL	2725	160	1580	479	47	30km/h
											40km/h
											50km/h
											10km/h
											30km/h
480/70R38	BLA02	145/142	A8/B	W14L W15L W16L	TL	2900	160	1681	479	47	30km/h
											40km/h
											50km/h
											10km/h
											30km/h
520/70R38	BLA02	150/150	A8/B	W15L W16L W18L	TL	3350	160	1749	516	48	30km/h
											40km/h
											50km/h
											10km/h
											30km/h
580/70R38	BLA02	155/155	A8/B	W18L	TL	3875	160	1827	577	50	30km/h
											40km/h
											50km/h
											10km/h
											30km/h
	BLA02	170/167	A8/B	W18L	TL	6000	280	1827	577	50	40km/h
											50km/h
											10km/h
											30km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
1470	1710	1950	2190	2430	2675					
1210	1405	1605	1800	2000	2200					
1130	1315	1500	1685	1870	2060					
1045	1215	1385	1555	1725	1900					
1480	1700	1955	2205	2460	2710	2965	3155			
1220	1400	1610	1820	2025	2235	2440	2600			
1140	1310	1505	1700	1895	2085	2280	2430			
1050	1205	1385	1565	1745	1925	2105	2240			
1685	1960	2235	2510	2785	3065					
1385	1615	1840	2070	2295	2525					
1295	1510	1720	1935	2145	2360					
1195	1395	1590	1785	1980	2180					
1785	2080	2370	2665	2955	3250					
1470	1710	1950	2190	2430	2675					
1375	1600	1825	2050	2275	2500					
1265	1470	1675	1885	2090	2300					
1770	2035	2335	2635	2940	3240	3540	3770			
1455	1670	1920	2170	2415	2665	2910	3100			
1360	1565	1795	2030	2260	2490	2725	2900			
1245	1430	1640	1855	2065	2275	2490	2650			
1745	2060	2375	2645	2960	3225	3540	3810	4170	4485	
1435	1695	1955	2175	2435	2655	2915	3135	3430	3690	
1345	1585	1825	2035	2275	2480	2725	2930	3205	3450	
1225	1445	1665	1855	2075	2265	2485	2675	2925	3150	
1945	2265	2580	2900	3220	3540					
1600	1865	2125	2390	2650	2915					
1495	1740	1985	2230	2475	2725					
1495	1740	1985	2230	2475	2725					
2070	2410	2750	3090	3430	3770					
1705	1980	2260	2540	2820	3100					
1595	1855	2115	2375	2635	2900					
1455	1695	1930	2170	2410	2650					
2395	2785	3175	3570	3960	4355					
1965	2290	2610	2935	3255	3580					
1840	2140	2445	2745	3045	3350					
1840	2140	2445	2745	3045	3350					
2765	3220	3675	4125	4580	5035					
2275	2650	3025	3395	3770	4145					
2130	2480	2825	3175	3525	3875					
2130	2480	2825	3175	3525	3875					
3350	3900	4445	4990	5535	6080	6705	7095	7800		
2760	3210	3655	4105	4555	5005	5520	5840	6420		
2580	3000	3420	3840	4260	4680	5160	5460	6000		
2340	2725	3105	3485	3865	4250	4685	4955	5450		



BLA03

R-1W

- ✓ The tread pattern ensures excellent self-cleaning.
- ✓ Maximum traction and outstanding productivity thanks to a large contact patch.
- ✓ Capable of comfortably working at speeds up to 65km/h.

AVAILABLE SIZES

440/65R24	540/65R24	540/65R38	650/65R38
440/65R28	540/65R28	600/65R28	650/65R42
480/65R24	540/65R30	600/65R34	710/70R38
480/65R28	540/65R34	600/65R38	710/70R42



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
440/65R24	BLA03	128/131	D/A8	W13 W14L W15L	TL	1800	160	1182	441	45	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
440/65R28	BLA03	131/134	D/A8	W13 W14L W15L	TL	1950	160	1283	441	45	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
480/65R24	BLA03	133/136	D/A8	W14L W15L	TL	2060	160	1234	479	46	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
480/65R28	BLA03	136/139	D/A8	W14L W15L	TL	2240	160	1335	479	46	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
540/65R24	BLA03	140/143	D/A8	W16L W18L	TL	2500	160	1312	550	48	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
540/65R28	BLA03	142/145	D/A8	W16L W18L	TL	2650	160	1413	550	48	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
540/65R30	BLA03	150/153	D/A8	W16L W18L	TL	3350	240	1464	550	48	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
540/65R34	BLA03	145/148	D/A8	W16L W18L	TL	2900	160	1566	550	48	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg											
60	80	100	120	140	160	200	240	280	320	360	
1310	1540	1755	1965	2150	2340						
1155	1365	1550	1735	1900	2070						
1090	1285	1460	1635	1790	1950						
1055	1245	1415	1585	1735	1890						
1005	1185	1350	1510	1655	1800						
1415	1670	1900	2125	2330	2535						
1250	1475	1680	1880	2060	2240						
1185	1395	1590	1780	1950	2120						
1145	1345	1530	1715	1880	2045						
1090	1285	1460	1635	1790	1950						
1495	1765	2005	2245	2460	2675						
1320	1560	1770	1985	2175	2365						
1250	1475	1680	1880	2060	2240						
1205	1425	1620	1810	1985	2160						
1150	1355	1545	1730	1895	2060						
1625	1920	2180	2440	2675	2910						
1440	1695	1930	2160	2365	2575						
1360	1600	1820	2040	2235	2430						
1315	1550	1760	1970	2160	2350						
1250	1475	1680	1880	2060	2240						
1820	2145	2435	2730	2990	3250						
1610	1895	2155	2415	2645	2875						
1525	1795	2040	2285	2505	2725						
1470	1730	1965	2205	2415	2625						
1400	1650	1875	2100	2300	2500						
1925	2270	2580	2890	3165	3445						
1705	2005	2280	2555	2800	3045						
1620	1910	2175	2435	2665	2900						
1555	1830	2085	2335	2555	2780						
1480	1745	1985	2225	2435	2650						
2045	2395	2740	3045	3350	3610	4050	4355				
1805	2115	2425	2695	2960	3195	3580	3850				
1715	2005	2295	2555	2810	3025	3390	3650				
1650	1930	2210	2460	2705	2915	3265	3515				
1570	1840	2110	2345	2575	2780	3115	3350				
2110	2485	2825	3165	3465	3770						
1865	2200	2500	2800	3065	3335						
1760	2075	2360	2645	2895	3150						
1705	2005	2280	2555	2800	3045						
1620	1910	2175	2435	2665	2900						

Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
540/65R38	BLA03	153/156	D/A8	W16L W18L	TL	3650	240	1667	550	48	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/65R28	BLA03	147/150	D/A8	DW20B W18L	TL	3075	160	1491	591	52	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/65R34	BLA03	157/160	D/A8	DW20B W18L	TL	4125	240	1644	591	52	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/65R38	BLA03	153/156	D/A8	DW20B W18L	TL	3650	160	1745	591	52	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
650/65R38	BLA03	157/160	D/A8	DW20B	TL	4125	160	1811	645	56	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
650/65R42	BLA03	165/168	D/A8	DW20B	TL	5150	240	1913	645	56	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/70R38	BLA03	166/169	D/A8	DW23B	TL	5300	160	1959	716	57	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/70R42	BLA03	168/171	D/A8	DW23B	TL	5600	160	2061	716	57	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
	BLA03	173/176	D/A8	DW23B	TL	6500	240	2061	716	57	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
2230	2605	2985	3320	3650	3935	4410	4745			
1970	2305	2640	2935	3230	3480	3900	4195			
1880	2200	2520	2800	3080	3320	3720	4000			
1800	2105	2410	2680	2945	3175	3560	3830			
1715	2005	2295	2555	2810	3025	3390	3650			
2235	2635	2995	3355	3675	3995					
1975	2330	2650	2965	3250	3535					
1875	2210	2510	2810	3080	3350					
1805	2125	2415	2705	2965	3225					
1720	2025	2305	2580	2825	3075					
2515	2945	3375	3750	4125	4445	4980	5360			
2225	2605	2985	3315	3645	3930	4405	4740			
2115	2475	2835	3150	3465	3735	4185	4500			
2035	2380	2725	3030	3330	3590	4025	4330			
1935	2265	2595	2885	3175	3420	3835	4125			
2655	3130	3555	3985	4365	4745					
2345	2765	3145	3520	3855	4195					
2240	2640	3000	3360	3680	4000					
2140	2525	2870	3215	3520	3830					
2040	2405	2735	3065	3355	3650					
3000	3535	4020	4500	4930	5360					
2650	3125	3555	3980	4360	4740					
2520	2970	3375	3780	4140	4500					
2420	2855	3245	3635	3980	4330					
2310	2720	3090	3465	3795	4125					
3145	3680	4215	4685	5155	5555	6225	6695			
2780	3255	3725	4140	4555	4910	5505	5920			
2630	3080	3525	3920	4310	4645	5205	5600			
2540	2970	3405	3780	4160	4485	5025	5405			
2420	2830	3240	3605	3965	4270	4785	5150			
3785	4405	5025	5645	6265	6890					
3350	3900	4445	4995	5545	6095					
3190	3710	4230	4755	5275	5800					
3060	3560	4060	4560	5060	5565					
2915	3390	3865	4345	4820	5300					
4000	4655	5310	5965	6620	7280					
3540	4120	4700	5280	5860	6440					
3380	3935	4485	5040	5595	6150					
3230	3760	4290	4820	5350	5880					
3080	3580	4085	4590	5095	5600					
3970	4560	5235	5915	6590	7265	7940	8450			
3510	4035	4630	5230	5830	6425	7025	7475			
3335	3830	4400	4970	5535	6105	6670	7100			
3205	3685	4230	4775	5320	5865	6415	6825			
3055	3510	4030	4550	5070	5590	6110	6500			

BLA07

R-1W

- ✓ A flat stable tread spreads the load evenly across the footprint, helping to minimize soil compaction by providing excellent ground pressure distribution.
- ✓ Extremely economical thanks to very good traction and low-wear tread compound.
- ✓ Long tire life through optimized tread pattern design and high resistance to damage.

AVAILABLE SIZES

600/70R28	600/70R34	800/70R38
600/70R30	650/60R34	
620/70R42	710/55R30	
650/85R38	710/75R42	



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
600/70R28	BLA07	157	D	DW18L DW20B W18L	TL	4125	240	1551	591	52.5	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/70R30	BLA07	161/161	A8/B	DW18L DW20B W18L	TL	4625	280	1551	591	52.5	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/70R34	BLA07	152	D	DW18L DW20B W18L	TL	3550	160	1602	591	52.5	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
620/70R42	BLA07	172	D	DW18L W18L DW20B	TL	6300	320	1935	625	58	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
650/85R38	BLA07	173/176	D/A8	DW20B DW21B DW23B	TL	6500	240	2071	645	65	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/70R34	BLA07	160/163	D/A8	DW18L DW20B W18L	TL	4500	240	1704	601	52	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
650/60R34	BLA07	159/162	D/A8	DW20B DW21B DW23B	TL	4375	240	1644	645	52	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg											
60	80	100	120	140	160	200	240	280	320	360	
2515	2890	3320	3750	4180	4605	5035	5360				
2225	2555	2935	3315	3695	4075	4455	4740				
2120	2435	2795	3160	3520	3880	4240	4515				
2035	2335	2680	3030	3375	3720	4070	4330				
1935	2225	2555	2885	3215	3545	3875	4125				
2580	3005	3425	3845	4265	4685	5165	5465	6010			
2125	2470	2815	3160	3510	3855	4250	4495	4945			
1985	2310	2635	2960	3280	3605	3975	4205	4625			
1985	2310	2635	2960	3280	3605	3975	4205	4625			
2535	2950	3365	3780	4195	4615						
2240	2610	2975	3345	3710	4080						
2135	2485	2835	3185	3535	3885						
2045	2380	2715	3050	3385	3725						
1950	2270	2590	2910	3230	3550						
2595	2980	3425	3865	4305	4750	5190	5525				
2295	2635	3025	3415	3810	4200	4590	4885				
2185	2510	2880	3255	3625	3995	4370	4650				
2095	2405	2765	3120	3475	3835	4190	4460				
1995	2295	2635	2975	3315	3655	3995	4250				
3190	3765	4340	4830	5405	5895	6470	6960	7615	8190		
2825	3330	3835	4270	4780	5215	5720	6155	6735	7245		
2685	3170	3650	4065	4550	4960	5445	5860	6410	6895		
2575	3040	3505	3900	4365	4760	5225	5620	6150	6615		
2455	2895	3335	3715	4155	4535	4975	5355	5855	6300		
3970	4560	5235	5915	6590	7265	7940	8450				
3510	4035	4630	5230	5830	6425	7025	7475				
3335	3830	4400	4970	5535	6105	6670	7100				
3205	3685	4230	4775	5320	5865	6415	6825				
3055	3510	4030	4550	5070	5590	6110	6500				
2745	3155	3625	4095	4560	5030	5495	5850				
2430	2790	3205	3620	4035	4450	4860	5175				
2290	2630	3020	3410	3800	4190	4580	4875				
2220	2550	2925	3305	3685	4060	4440	4725				
2115	2430	2790	3150	3510	3870	4230	4500				
2615	3010	3465	3865	4320	4715	5285	5685				
2310	2665	3065	3420	3820	4170	4675	5030				
2185	2515	2895	3230	3610	3940	4415	4750				
2110	2430	2795	3120	3485	3805	4265	4590				
2010	2315	2665	2975	3325	3630	4065	4375				

Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
710/55R30	BLA07	153/156	D/A8	DW23B DW24B	TL	3650	160	1544	706	51	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/75R42	BLA07	181/184	D/A8	DW20B DW21B DW23B DW24B DW25B	TL	8250	320	2133	706	63	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
800/70R38	BLA07	178/181	D/A8	DW25B DW27B	TL	7500	240	2085	798	62	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
2605	3035	3460	3890	4315	4745					
2305	2680	3060	3435	3815	4195					
2200	2560	2920	3280	3640	4000					
2105	2450	2795	3140	3485	3830					
2005	2335	2660	2990	3320	3650					
4180	4930	5680	6325	7075	7720	8470	9115	9970	10725	
3695	4360	5025	5595	6260	6825	7490	8060	8820	9485	
3510	4140	4770	5310	5940	6480	7110	7650	8370	9000	
3375	3980	4585	5105	5715	6235	6840	7360	8050	8660	
3215	3795	4370	4865	5445	5940	6515	7010	7670	8250	
4580	5265	6045	6825	7605	8385	9165	9750			
4050	4655	5345	6035	6725	7415	8105	8625			
3875	4455	5115	5775	6435	7095	7755	8250			
3700	4250	4880	5510	6140	6770	7400	7875			
3525	4050	4650	5250	5850	6450	7050	7500			



BLA05

R-1W

- ✓ Reinforced shoulder contributes to better sidewall protection and an extended tire life.
- ✓ Super flat tread and large footprint help reduce soil compaction.
- ✓ Strong but flexible casing delivers exceptional ride and comfort.

AVAILABLE SIZES

650/75R32	800/65R32
710/60R34	
750/65R26	
800/70R32	



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
650/75R32	BLA05	172/172	A8/B	DW20B DW21B DW23B	TL	6300	320	1789	645	59	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/60R34	BLA05	164/167	D/A8	DW21B DW23B DW24B DW25B	TL	5000	240	1716	716	58	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
750/65R26	BLA05	171/171	A8/B	DW23B DW24B DW25B	TL	6150	320	1636	754	50	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
800/70R32	BLA05	181/181	A8/B	DW25B DW27B DH27B	TL	8250	320	1933	798	57	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
800/65R32	BLA05	181/181	A8/B	DW25B DW27B DH27B	TL	8250	360	1853	798	58	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
3190	3765	4340	4830	5405	5895	6470	6960	7615	8190	
2625	3100	3570	3975	4445	4850	5320	5725	6265	6740	
2455	2895	3335	3715	4155	4535	4975	5355	5855	6300	
2455	2895	3335	3715	4155	4535	4975	5355	5855	6300	
2990	3445	3965	4420	4940	5395	6045	6500			
2645	3045	3505	3910	4370	4770	5345	5750			
2505	2885	3320	3705	4140	4520	5065	5450			
2415	2780	3200	3570	3990	4355	4880	5250			
2300	2650	3050	3400	3800	4150	4650	5000			
3195	3675	4235	4795	5195	5675	6315	6795	7435	7995	
2630	3025	3485	3945	4275	4670	5195	5590	6115	6580	
2460	2825	3255	3690	3995	4365	4855	5225	5715	6150	
2460	2825	3255	3690	3995	4365	4855	5225	5715	6150	
4180	4930	5680	6325	7075	7720	8470	9115	9970	10725	
3440	4055	4675	5205	5820	6350	6970	7500	8205	8825	
3215	3795	4370	4865	5445	5940	6515	7010	7670	8250	
3215	3795	4370	4865	5445	5940	6515	7010	7670	8250	
3860	4500	5145	5895	6540	7185	7935	8365	9220	9970	
3175	3705	4235	4850	5380	5910	6530	6880	7585	8205	
2970	3465	3960	4535	5030	5525	6105	6435	7095	7670	
2970	3465	3960	4535	5030	5525	6105	6435	7095	7670	



AGRIHARVEST BLA09

R-1W

- ✓ Carry up to 40% more load at same pressure versus non-VF radial tire of the same size.
- ✓ Wide footprint creating broader contact area with the soil.
- ✓ Reinforced structure resistant to punctures and cuts.

AVAILABLE SIZES

- VF520/85R42
- VF600/60R30
- VF900/60R32
- VF900/60R38



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
VF 520/85R42	AgriHarvest BLA09	177	A8	DW18L	TL	7300	280	1951	516	52	40km/h
VF 600/60R30	AgriHarvest BLA09	162	D	DW20B DW21B	TL	4750	200	1482	597	52	65km/h
VF 900/60R32	AgriHarvest BLA09	191	A8	DW30B	TL	10900	280	1893	891	56	40km/h
VF 900/60R38	AgriHarvest BLA09	193	A8	DW30B	TL	11500	280	2045	891	58	40km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
3135	3650	4160	4670	5180	5690	6275	6640	7300		
2325	2705	3135	3515	3895	4275	4750				
4685	5450	6210	6975	7735	8500	9370	9915	10900		
4945	5750	6555	7360	8165	8970	9890	10465	11500		



BLA01

R-1 / R-1W

- ✓ Deep lugs, low slip and optimized rubber compounds help reduce wear for exceptionally long tire life.
- ✓ Good self-cleaning properties help keep the tread pattern free of mud, resulting in less slip, even in difficult conditions.
- ✓ Multiple types of rubber are designed with tread compound, providing excellent wear and fatigue resistance.

AVAILABLE SIZES

380/90R46

320/90R46



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
380/90R46	BLA01	157/157	A8/B	W11 W12 W13	TL	4125	360	1852	380	45	10km/h
											30km/h
											40km/h
											50km/h
											10km/h
320/90R46	BLA01	146/143	A8/B	Wg W10 W11	TL	3000	320	1744	319	37	30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
1980	2300	2625	3000	3320	3640	4020	4230	4660	5035	
1630	1895	2160	2465	2730	2995	3305	3480	3835	4145	
1525	1770	2020	2310	2555	2805	3090	3255	3585	3875	
1525	1770	2020	2310	2555	2805	3090	3255	3585	3875	
1520	1790	2065	2300	2570	2805	3080	3315	3625	3900	
1250	1475	1700	1890	2115	2310	2535	2725	2985	3210	
1170	1380	1590	1770	1980	2160	2370	2550	2790	3000	
1060	1250	1440	1605	1795	1960	2150	2315	2530	2725	

BLA08

R-1 / R-1W

- ✓ Deep lugs provide excellent traction, better directional stability and a high level of control.
- ✓ An extra-strong but super-flexible casing, which offers a large footprint and surprising ride comfort, has excellent durability to carry extra-heavy loads.

AVAILABLE SIZES

320/90R42

380/90R50



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
320/90R42	BLA08	147/147	A8/B	W9 W10 W11	TL	3075	400	1643	319	37	10km/h
											30km/h
											40km/h
											50km/h
380/90R50	BLA08	160/157	A8/B	W11 W12 W13	TL	4500	400	1954	380	48	10km/h
											30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
1395	1635	1875	2115	2355	2555	2835	2995	3275	3555	
1150	1345	1545	1740	1940	2105	2335	2465	2695	2925	
1075	1260	1445	1625	1810	1965	2180	2305	2520	2735	
1075	1260	1445	1625	1810	1965	2180	2305	2520	2735	
2045	2395	2745	3100	3450	3740	4150	4385	4795	5205	
1685	1970	2260	2550	2840	3080	3415	3610	3945	4285	
1575	1845	2115	2385	2655	2880	3195	3375	3690	4005	
1440	1690	1935	2185	2430	2640	2925	3090	3380	3670	

BLAF1

I-3

- ✓ Solid rounded shoulders increases maneuverability and reduces scrub.
- ✓ Extremely economical thanks to very good traction and low-wear tread compound.
- ✓ Even distribution of ground pressure to minimize rutting and soil damage.

AVAILABLE SIZES

- 600/50R22.5 IMP
- 650/65R30.5 IMP
- 850/50R30.5 IMP



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
600/50R 22.5 IMP	BLAF1	159	D	AG20.00	TL	4375	400	1172	611	25	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
650/65R 30.5 IMP	BLAF1	176	D	AG20.00	TL	7100	400	1621	645	32	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
850/50R 30.5 IMP	BLAF1	182	D	AG28.00	TL	8500	400	1625	862	32	10km/h
											30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
120	160	200	240	280	320	360	400	450	500	550
3385	4095	4565	5275	5985	6535	7165	7875			
2840	3430	3830	4425	5015	5480	6010	6605			
2555	3090	3450	3985	4520	4935	5410	5950			
2270	2750	3065	3540	4020	4390	4810	5290			
1880	2275	2535	2930	3325	3630	3980	4375			
5495	6645	7410	8560	9710	10605	11625	12780			
4605	5570	6215	7180	8145	8895	9755	10720			
4150	5020	5595	6465	7335	8010	8785	9655			
3690	4465	4980	5755	6525	7125	7815	8590			
3050	3690	4115	4755	5395	5890	6460	7100			
6575	7955	8870	10250	11625	12695	13920	15300			
5515	6670	7440	8595	9750	10650	11675	12835			
4970	6010	6700	7745	8785	9590	10515	11560			
4420	5345	5965	6890	7815	8535	9355	10285			
3655	4420	4930	5695	6460	7055	7735	8500			



BLF01

I-3

- ✓ With a large contact patch, this tire offers max flotation and soil protection.
- ✓ Solid rounded shoulders for greater resistance to irregular wear, reduced scrub and improved maneuverability.
- ✓ Steel belted design increases load capacity and resistance to impacts.

AVAILABLE SIZES

500/50R17 IMP	600/50R22.5 IMP	710/50R30.5 IMP
500/45R22.5 IMP	600/55R26.5 IMP	750/45R26.5 IMP
500/60R22.5 IMP	650/55R26.5 IMP	750/60R30.5 IMP
560/45R22.5 IMP	650/65R26.5 IMP	800/45R26.5 IMP
560/60R22.5 IMP	710/50R26.5 IMP	800/45R30.5 IMP
580/65R22.5 IMP	710/45R22.5 IMP	



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
500/50R17 IMP	BLF01	149	D	16.00	TL	3250	500	932	503	15	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
500/45R22.5 IMP	BLF01	146	D	AG16.00	TL	3000	400	1022	503	21	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
500/60R22.5 IMP	BLF01	155	D	AG16.00	TL	3875	400	1172	503	18	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
560/45R22.5 IMP	BLF01	152	D	AG16.00	TL	3550	400	1076	543	18	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
560/45R22.5 IMP	BLF01	165	D	AG16.00	TL	5150	500	1244	543	18	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
580/65R22.5 IMP	BLF01	166	D	AG18.00	TL	5300	400	1326	577	21	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/50R22.5 IMP	BLF01	163	D	AG18.00	TL	4875	500	1172	591	21	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
600/55R26.5 IMP	BLF01	165	D	AG20.00	TL	5150	400	1333	591	20	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg											
120	160	200	240	280	320	360	400	450	500	550	
2220	2690	2980	3450	3915	4325	4735	5205	5555	5850		
1860	2255	2500	2890	3285	3625	3970	4365	4655	4905		
1675	2030	2250	2605	2960	3270	3580	3930	4195	4420		
1490	1805	2000	2315	2630	2905	3180	3495	3730	3930		
1235	1495	1655	1915	2175	2405	2630	2890	3085	3250		
2320	2805	3130	3615	4100	4480	4910	5400				
1945	2355	2625	3035	3440	3755	4120	4530				
1750	2120	2365	2730	3100	3385	3710	4080				
1560	1885	2105	2430	2755	3010	3300	3630				
1290	1560	1740	2010	2280	2490	2730	3000				
2995	3625	4045	4670	5300	5785	6345	6975				
2515	3040	3390	3915	4445	4855	5320	5850				
2265	2740	3055	3530	4005	4370	4795	5270				
2010	2435	2715	3135	3560	3885	4260	4685				
1665	2015	2245	2595	2945	3215	3525	3875				
2745	3320	3705	4280	4855	5300	5810	6390				
2300	2785	3105	3590	4070	4445	4875	5360				
2070	2505	2795	3230	3665	4000	4390	4825				
1845	2230	2490	2875	3260	3560	3905	4295				
1525	1845	2055	2375	2695	2945	3230	3550				
3520	4260	4725	5465	6210	6855	7505	8250	8805	9270		
2950	3575	3965	4585	5205	5750	6295	6915	7385	7775		
2660	3220	3570	4130	4690	5180	5670	6230	6650	7000		
2365	2865	3175	3675	4170	4610	5045	5540	5915	6230		
1955	2365	2625	3035	3450	3810	4170	4580	4890	5150		
4100	4960	5530	6390	7250	7915	8680	9540				
3440	4160	4640	5360	6080	6640	7280	8000				
3095	3745	4175	4825	5475	5980	6555	7205				
2755	3330	3715	4290	4870	5320	5830	6410				
2275	2755	3070	3550	4025	4395	4820	5300				
3330	4035	4475	5175	5875	6490	7105	7805	8335	8775		
2795	3385	3750	4340	4930	5445	5960	6550	6990	7360		
2515	3045	3380	3910	4440	4905	5370	5900	6295	6630		
2240	2710	3005	3475	3945	4360	4770	5245	5600	5895		
1850	2240	2485	2875	3265	3605	3945	4335	4630	4875		
3985	4820	5375	6210	7045	7690	8435	9270				
3340	4040	4505	5205	5905	6450	7075	7775				
3010	3640	4060	4690	5320	5810	6370	7000				
2675	3235	3610	4170	4730	5170	5665	6230				
2210	2675	2985	3450	3910	4270	4685	5150				

Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
650/55R 26.5 IMP	BLF01	169	D	AG20.00	TL	5800	400	1389	645	24	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
650/65R 26.5 IMP	BLF01	174	D	AG20.00	TL	6700	400	1519	645	24	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/50R 26.5 IMP	BLF01	170	D	AG24.00	TL	6000	400	1383	727	24	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/45R22.5 IMP	BLF01	165	D	AG22.00	TL	5150	400	1212	706	25	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
710/50R 30.5 IMP	BLF01	173	D	AG24.00	TL	6500	400	1485	727	26	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
750/45R26.5 IMP	BLF01	170	D	22.00 AG24.00 AG28.00	TL	6000	400	1349	754	25	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
750/60R 30.5 IMP	BLF01	181	D	AG24.00	TL	8250	400	1675	754	26	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
800/45R 26.5 IMP	BLF01	174	D	AG26.00	TL	6700	400	1393	808	26	10km/h
											30km/h
											40km/h
											50km/h
											65km/h
800/45R 30.5 IMP	BLF01	176	D	AG26.00	TL	7100	400	1495	808	26	10km/h
											30km/h
											40km/h
											50km/h
											65km/h

Pressure(kPa)-Load per tyre in kg										
60	80	100	120	140	160	200	240	280	320	360
4485	5425	6055	6990	7930	8665	9500	10440			
3760	4550	5075	5865	6650	7265	7965	8755			
3390	4100	4570	5280	5990	6540	7175	7885			
3015	3645	4065	4700	5330	5820	6380	7015			
2490	3015	3360	3885	4405	4810	5275	5800			
5185	6270	6990	8080	9165	10005	10970	12060			
4345	5255	5865	6775	7685	8395	9200	10115			
3915	4735	5280	6100	6920	7560	8290	9110			
3485	4210	4700	5430	6155	6725	7375	8105			
2880	3480	3885	4485	5090	5560	6095	6700			
4640	5615	6260	7235	8205	8960	9825	10800			
3895	4710	5250	6070	6885	7515	8240	9060			
3505	4240	4730	5465	6200	6770	7425	8160			
3120	3775	4210	4860	5515	6025	6605	7260			
2580	3120	3480	4020	4560	4980	5460	6000			
3985	4820	5375	6210	7045	7690	8435	9270			
3340	4040	4505	5205	5905	6450	7075	7775			
3010	3640	4060	4690	5320	5810	6370	7000			
2675	3235	3610	4170	4730	5170	5665	6230			
2210	2675	2985	3450	3910	4270	4685	5150			
5030	6080	6785	7835	8890	9710	10645	11700			
4220	5100	5690	6575	7455	8145	8930	9815			
3800	4595	5125	5920	6715	7335	8040	8840			
3380	4085	4560	5265	5975	6525	7155	7865			
2795	3380	3770	4355	4940	5395	5915	6500			
4640	5615	6260	7235	8205	8960	9825	10800			
3895	4710	5250	6070	6885	7515	8240	9060			
3505	4240	4730	5465	6200	6770	7425	8160			
3120	3775	4210	4860	5515	6025	6605	7260			
2580	3120	3480	4020	4560	4980	5460	6000			
6385	7720	8610	9945	11285	12325	13510	14850			
5355	6475	7220	8340	9465	10335	11330	12455			
4820	5830	6505	7515	8525	9310	10210	11220			
4290	5185	5785	6685	7580	8280	9080	9980			
3545	4290	4785	5525	6270	6845	7505	8250			
5185	6270	6990	8080	9165	10005	10970	12060			
4345	5255	5865	6775	7685	8395	9200	10115			
3915	4735	5280	6100	6920	7560	8290	9110			
3485	4210	4700	5430	6155	6725	7375	8105			
2880	3480	3885	4485	5090	5560	6095	6700			
5495	6645	7410	8560	9710	10605	11625	12780			
4605	5570	6215	7180	8145	8895	9755	10720			
4150	5020	5595	6465	7335	8010	8785	9655			
3690	4465	4980	5755	6525	7125	7815	8590			
3050	3690	4115	4755	5395	5890	6460	7100			

BLT03

AVAILABLE SIZES

385/55R19.5

435/50R19.5

445/45R19.5



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
385/55R19.5	BLT03	156	D	12.25	TL	4000	900	919	386	12.5	
435/50R19.5	BLT03	160	D	14.00	TL	4500	900	931	438	12.5	
445/45R19.5	BLT03	160	D	15.00	TL	4500	900	895	446	15.5	

Pressure(kPa)-Load per tyre in kg										
120	160	200	240	280	320	360	400	450	500	550

BL606

AVAILABLE SIZES

425/65R22.5

445/65R22.5



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
425/65R22.5	BL606	165	D	13.00	TL	5150	825	1124	430	175	
445/65R22.5	BL606	169	D	14.00	TL	5800	900	1150	444	18	

Pressure(kPa)-Load per tyre in kg										
120	160	200	240	280	320	360	400	450	500	550

BLA04

R-4

- ✓ Extra-deep 40° lugs provide impressive traction and excellent directional control.
- ✓ Reinforced centreline undertread for tread penetration resistance.

AVAILABLE SIZES

460/70R24 IND

500/70R24 IND



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
460/70R24 IND	BLA04	159/159	A8/B	DW14L DW15L DW16L	TL	4375	400	1254	455	36	0km/h
											10km/h
											30km/h
											40km/h
											50km/h
500/70R24 IND	BLA04	164/164	A8/B	DW16L DW15L	TL	5000	400	1310	503	39	0km/h
											10km/h
											30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
120	160	200	240	280	320	360	400	450	500	550
4225	5130	5630	6535	7440	8345	9150	10060			
2295	2785	3060	3550	4040	4535	4970	5465			
1910	2320	2545	2955	3365	3775	4140	4550			
1835	2230	2450	2840	3235	3630	3980	4375			
1835	2230	2450	2840	3235	3630	3980	4375			
4830	5865	6440	7475	8510	9545	10465	11500			
2625	3185	3500	4060	4625	5185	5685	6250			
2180	2650	2910	3380	3845	4315	4730	5200			
2100	2550	2800	3250	3700	4150	4550	5000			
2100	2550	2800	3250	3700	4150	4550	5000			

BLA06

R-4 Radial

- ✓ Extremely economical thanks to very good traction and low-wear tread compound.
- ✓ Excellent grip on hard surfaces due to new block pattern designed for pure industrial applications.

AVAILABLE SIZES

400/70R18 IND

400/70R20 IND

500/70R24 IND



Size	Pattern	L/S-index	Speed Symbols	Rim	TT/TL	Maxload (kg)	Inflated pressure (kPa)	Inflated Dimensions		Tread depth (mm)	kPa
								OD (mm)	ID (mm)		
400/70R18 IND	BLA06	147/147	A8/B	13.00	TL	3075	400	1017	404	23	0km/h
											10km/h
											30km/h
											40km/h
											50km/h
400/70R20 IND	BLA06	149/149	A8/B	13.00	TL	3250	400	1068	404	23	0km/h
											10km/h
											30km/h
											40km/h
											50km/h
500/70R24 IND	BLA06	164/164	A8/B	DW16L DW15L	TL	5000	400	1310	503	28	0km/h
											10km/h
											30km/h
											40km/h
											50km/h

Pressure(kPa)-Load per tyre in kg										
120	160	200	240	280	320	360	400	450	500	550
2965	3605	3955	4595	5230	5865	6430	7070			
1610	1955	2150	2495	2840	3185	3490	3840			
1340	1625	1785	2075	2360	2650	2905	3195			
1290	1565	1720	1995	2275	2550	2795	3075			
1290	1565	1720	1995	2275	2550	2795	3075			
3135	3810	4185	4855	5530	6200	6800	7475			
1705	2070	2270	2635	3000	3365	3690	4060			
1415	1720	1890	2195	2500	2805	3075	3380			
1365	1655	1820	2110	2405	2695	2955	3250			
1365	1655	1820	2110	2405	2695	2955	3250			
4830	5865	6440	7475	8510	9545	10465	11500			
2625	3185	3500	4060	4625	5185	5685	6250			
2180	2650	2910	3380	3845	4315	4730	5200			
2100	2550	2800	3250	3700	4150	4550	5000			
2100	2550	2800	3250	3700	4150	4550	5000			

Good quality OTR tires providing a better road contact for improved driving comfort and lower fuel consumption.

Flexible tires, which are strong and capable of effectively dealing with shocks from the road surface.

These are the properties offered by our wide range of radial OTR tires.

Barkley's diagonal tires ensure high vehicle stability and higher resistance against damage to the tire's side walls.

**OTR/
OFF-ROAD**



BLB01

- ✓ Exceptional traction and manoeuvrability.
- ✓ Good flotation.
- ✓ Excellent stability and comfort.

AVAILABLE SIZES

17.5R25	29.5R25
20.5R25	
23.5R25	
26.5R25	



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
17.5R25	BLB01	★★	E3/L3	167/182	B/A2	TL	14.00/15	8500	5450	650
20.5R25	BLB01	★★	E3/L3	177/193	B/A2	TL	17.00/2.0	11500	7300	650
23.5R25	BLB01	★★	L3,C1	201	A2	TL	19.50/2.5	14500		650
26.5R25	BLB01	★★	L3,C1	209	A2	TL	22.00/3.0	18500		650
29.5R25	BLB01	★★	L3,C1	216	A2	TL	25.00/3.5	22400		650

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
440	1330	599	4057	27
510	1476	664	4502	30
590	1600	720	4880	33
662	1730	779	5277	36
724	1873	843	5713	39

BLB05S

- ✓ Good traction and wear resistance.
- ✓ Excellent tear resistance.

AVAILABLE SIZES

750/65R25
29.5R25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
750/65R25	BLB05S	★★	L3	209	A2	TL	24.00/3.0	18500		625
29.5R25	BLB05S	★★	L3	200/216	B/A2	TL	25.00/3.5	22400	14000	650

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
746	1600	720	4880	45
750	1921	864	5859	45



LOADERS & DOZERS

BLB06S+

- ✓ Exceptionally robust in masacre conditions. Excellent compromise of adhesion and traction.
- ✓ A substantial crown, robust shoulders reinforced with a protection band make up a tyre particularly resistant to shock ruptures, cuts and tread tearing.
- ✓ A particularly resilient casing with the addition of several specific steel belts constitute a tyre that is very resistant to punctures.

AVAILABLE SIZES

17.5R25	29.5R25
20.5R25	
23.5R25	
26.5R25	



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
17.5R25	BLB06S+	★★	L5	167/182	B/A2	TL	14.00/1.5	8500	5450	650
20.5R25	BLB06S+	★★	L5	177/193	B/A2	TL	17.00/2.0	11500	7300	650
23.5R25	BLB06S+	★★	L5	185/201	B/A2	TL	19.50/2.5	14500	9250	650
26.5R25	BLB06S+	★★	L5	193/209	B/A2	TL	22.00/3.5	18500	11500	650
29.5R25	BLB06S+	★★	L5	200/216	B/A2	TL	25.00/3.5	22400	14000	650

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
445	1399	630	4267	63
520	1548	697	4721	70
597	1673	753	5103	76
673	1798	809	5484	85
750	1921	864	5859	92



LOADERS & DOZERS

BLB07S+

- ✓ Exceptional traction, high efficiency and optimum operating comfort.
- ✓ The extra deep tread pattern (L5) of this tyre gives outstanding wear life potential.
- ✓ The sidewall/tread intersection design gives an excellent level of damage and cut resistance.
- ✓ A wide, square tread gives better stability in loading operations and whilst travelling.

AVAILABLE SIZES

20.5R25
23.5R25
26.5R25
29.5R25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
20.5R25	BLB07S+	★★	L5	177/193	B/A2	TL	17.00/2.0	11500	7300	650
23.5R25	BLB07S+	★★	L5	185/201	B/A2	TL	19.50/2.5	14500	9250	650
26.5R25	BLB07S+	★★	L5	193/209	B/A2	TL	22.00/3.0	18500	11500	650
29.5R25	BLB07S+	★★	L5	200/216	B/A2	TL	25.00/3.5	22400	14000	650

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
520	1548	697	4721	70
597	1673	753	5103	76
673	1798	809	5484	85
750	1921	864	5859	92



LOADERS & DOZERS

BBE01

- ✓ Available for loaders and dozers.
- ✓ Wear and puncture resistance.
- ✓ Wide application.

AVAILABLE SIZES

15.5-25	20.5-25
16.00-25	23.5-25
17.5-25	26.5-25
20.5-25	29.5-25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
15.5-25	BBE01	12PR	E-3/L-3	-	-	TL	12.00/13	5600	3250	400
16.00-25	BBE01	28PR	E-3/L-3	-	-	TT/TL	11.25/2.0	11500	6700	750
17.5-25	BBE01	16PR	E-3/L-3	-	-	TT/TL	14.00/1.5	7300	4250	475
20.5-25	BBE01	16PR	E-3/L-3	-	-	TT/TL	17.00/2.0	8250	5450	350
20.5-25	BBE01	20PR	E-3/L-3	-	-	TT/TL	17.00/2.0	9500	6000	450
23.5-25	BBE01	20PR	E-3/L-3	-	-	TT/TL	19.50/2.5	10900	7300	375
26.5-25	BBE01	28PR	E-3/L-3	-	-	TT/TL	22.00/3.0	15500	10000	475
29.5-25	BBE01	28PR	E-3/L-3	-	-	TL	25.00/3.5	17500	11500	425

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
395	1275			25
430	1495			29
445	1350			26
520	1490			29
520	1490			29
595	1615			32
675	1750			35
750	1875			40



DUMP TRUCKS

BLB02S

- ✓ Exceptional traction and manoeuvrability.
- ✓ Good flotation.
- ✓ Excellent stability and comfort.

AVAILABLE SIZES

18.00R33



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
18.00R33	BLB02S		E-4 S1	191/209	B/A2	TL	13.00/2.5	18500	10900	800

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
478	1856	835	5661	52



BLB03S

- ✓ High safety.
- ✓ Wide contact area with ground provides strong grip.
- ✓ Low noise.

AVAILABLE SIZES

16.00R25
18.00R25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
16.00R25	BLB03S	★★★	E-4 S1	180	B	TL	11.25/2.0		8000	800
18.00R25	BLB03S		E-4 S1	185/204	B/A2	TL	13.00/2.5	16000	9250	800

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
432	1525	686	4651	42
493	1654	744	5045	46



BLM06S

- ✓ Exceptional traction, good self cleaning and optimum operating comfort.
- ✓ Massive tread blocks characterise this tyre, it delivers excellent tractive performance, better lateral adhesion and more efficient loading for machines working at the face.
- ✓ Flower chimb angle changed design.
- ✓ A wide, square tread gives better stability in loading operations and whilst travelling.

AVAILABLE SIZES

26.5R25
29.5R25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
26.5R25	BLM06S	★★	E4	193/209	B/A2	TL	22.00/3.0	18500	11500	650
29.5R25	BLM06S	★★	E4	200/216	B/A2	TL	25.00/3.5	22400	14000	650

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
673	1798	809	5484	85
750	1921	864	5859	60



SAND

BLD08

- ✓ Excellent traction performance.
- ✓ High temperature resistance: special compound designed for special desert road condition.
- ✓ Dual block pattern designed provides better flotation.

AVAILABLE SIZES

24R20.5



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
24R20.5	BLD08	★	E7	176	F	TL	18		7100	600

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
600	1370	615	4172	21



MOBILE CRANES

BLM02

- ✓ Exceptional traction and manoeuvrability.
- ✓ Good flotation.
- ✓ Excellent stability and comfort.

AVAILABLE SIZES

445/95R25

385/95R25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
445/95R25	BLM02			177	E	TL	11.25/2.0	7300		900
385/95R25	BLM02			170	E	TL	10.00/1.5	6000		900

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
430	1476	664	4502	23
370	1360	612	4148	21



BLM05

- ✓ Good traction and wear resistance.
- ✓ Excellent tear resistance.

AVAILABLE SIZES

16.00R20



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
16.00R20	BLM05			174/171	F	TL	11	6700/6150	760	

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
433	1318	593	4020	20



BBE02

- ✓ Good steer and traction.
- ✓ Off-road pattern has self-cleaning performance and comfort.

AVAILABLE SIZES

13.00-24



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
13.00-24	BBE02	12PR	G-2	-	-	TL	8.00TG	5600	2725	450

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
335	1280			24

BBE03

- ✓ Good steer and traction.
- ✓ Off-road pattern has self-cleaning performance and comfort.

AVAILABLE SIZES

15.5-25

17.5-25

20.5-25

23.5-25



Size	Pattern	Star/Rating	TRA Code	Load Index	Speed Index	TL/TT	Rim	Max Load (kg)		Inflated Pressure (kPa)
								10 km/h	50 km/h	
15.5-25	BBE03	12PR	E-2/L-2	-	-	TL	12.00/13	5600	3250	400
17.5-25	BBE03	16PR	E-2/L-2	-	-	TT/TL	14.00/15	7300	4250	475
20.5-25	BBE03	16PR	E-2/L-2	-	-	TT/TL	17.00/2.0	8250	5450	350
23.5-25	BBE03	16PR	E-2/L-2	-	-	TT/TL	19.50/2.5	9500	6150	300

Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)	Tread Depth (mm)
395	1275			24
445	1350			26
520	1490			29
595	1615			32



HEAD OFFICE
15F Mingzuo Mansion
No.111 Haibin
North Road
Weihai
China

T. +86 (0)631 5217918
E. cathy@barkleytire.com



barkleytire.com